



#### GENERAL

	<b>HB3 +100</b> 12V 60W P20d 9005 +100 12,8V 65W P20d +100 More Light	<b>Features</b>	original equipment manufacturer quality, high luminance, hardglass, UV-cut
	<b>Ordering Number</b> 27405	<b>Standard</b>	ECE R37 DOT
<b>Product Description</b>	halogen headlighting lamp	<b>Typical Applications</b>	high beam

#### TECHNICAL DETAILS

	<b>Rated Voltage</b>	ECE R37: 12V DOT: 12,8V	
	<b>Rated Wattage</b>	max. 73W @ 13,2V max. 70W @ 12,8V	
<b>Base</b>	P20d	<b>Operating Conditions</b>	burning position: horizontal, long electrode above filament
<b>Geometry</b>	Light center length: 31,5mm ± 0,2mm Bulb diameter: max. 12,5mm	<b>Luminous Flux</b>	1860 lm ± 12% @ 13,2V 1700 lm ± 12% @ 12,8V
<b>Lifetime</b>	B3: 155h @ 14,0V B50: 290h @ 14,0V Tc: 310h @ 14,0V		

#### DELIVERY DETAILS

<b>Packaging</b>	Commercial Box Packaging: 100pcs. (10×10×1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.
------------------	--	---

valid from 08/08/2018

replace for

file 27405 - HB3 +100 12V 60W P20d.100

**Disclaimer:**  
 Subject to change without notice. Errors and omission accepted.  
 Always make sure to use the most recent release.