

Product Information Sheet H27W/1 12V

GENERAL				
	H27W/1 12V 27W PG13	Features	original equipment manufacturer quality, hardglass, UV-cut	
	Ordering Number 28041	Standard	ECE R37	
Product Description	halogen headlighting lamp	Typical Applications	fog light	
TECHNICAL DETAILS				
Bezugsachse max.ø9 (reference axis)		Rated Voltage	ECE R37: 12V	
		Rated Wattage	max. 31W @13,5V	
38 max,44.5	31.75±0.5	Base	PG13	
89 89 89 80 80 80 80 80 80 80 80 80 80 80 80 80		Operating Conditions	burning position: horizontal	

		Luminous Flux	477 lm ± 15% @13,5V		
Geometry	Light center length: 31,75mm ± 0,5mm Bulb diameter: max. 9mm	Lifetime	B50: 900h @13,5V Lumen Maintenance: min. 85% after 225h @13,5V		
DELIVERY DETAILS					
Packaging	Industrial Packaging: 300pcs. (5×60) Commercial Box Packaging: 100pcs. (10×10×1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.			

valid from 12/04/2017

replace for 20.02.2013-V1-PN12/0250

file 28041 - H27W/1 12V 27W PG13.100

Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

vosla GmbH Plauen Germany www.vosla.com