

Product Information Sheet H27W/2 12V

GENERAL			
	H27W/2 12V 27W PGJ13	Features	original equipment manufacturer quality, hardglass, UV-cut
	Ordering Number 28042	Standard	ECE R37
Product Description	halogen headlighting lamp	Typical Applications	fog light
FECHNICAL DETAILS			
Bezugsachse (reference axis)	max.09	Rated Voltage	ECE R37: 12V
		Rated Wattage	max. 31W @13,5V
44.5	it it ui	Base	PGJ13

max.64		Rated Wattage	max. 31W @13,5V		
		Base	PGJ13		
		Operating Conditions	burning position: horizontal		
		Luminous Flux	477 lm ± 15% @13,5V		
Geometry	Light center length: 31,75mm ± 0,5mm Bulb diameter: max. 9mm	Lifetime	B50: 900h @13,5V Lumen Maintenance: min. 85% after 225h @13,5V		
DELIVERY DETAILS					
Industrial Packaging: 300pcs. (5×60)		Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture.			

For use in closed luminaires only.

valid from 12/04/2017

replace for 20.02.2013-V1-PN12/0250

Commercial Box Packaging:

100pcs. (10×10×1)

file 28042 - H27W/2 12V 27W PGJ13.100

Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

Packaging

vosla GmbH Plauen Germany www.vosla.com