



GENERAL

	H9 12V 65W PGJ19-5	Features	original equipment manufacturer quality, blue cover plate, hardglass, UV-cut
	Ordering Number 28077	Standard	ECE R37 DOT
Product Description	halogen headlighting lamp	Typical Applications	high beam

TECHNICAL DETAILS

	Rated Voltage	ECE R37: 12V	
	Rated Wattage	max. 73W @13,2V max. 70W @12,8V	
Base	PGJ19-5	Operating Conditions	burning position: horizontal, long electrode above filament
Geometry	Light center length: 25mm ± 0,25mm Bulb diameter: max. 12,5mm	Luminous Flux	2100 lm ± 10% @13,2V 2000 lm ± 240lm @12,8V
Lifetime	B3: 300h @13,2V Tc: 500h @13,2V		

DELIVERY DETAILS

Packaging	Industrial Packaging: 140pcs. (4×35) Commercial Box Packaging: 100pcs. (10×10×1)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.
------------------	---	---

valid from 12/04/2017

replace for 06.07.2016-V3-PN16/0245

file 28077 - H9 12V 65W PGJ19-5.100

Disclaimer:
 Subject to change without notice. Errors and omission accepted.
 Always make sure to use the most recent release.