



#### GENERAL

|  |                                 |                             |                                    |
|--|---------------------------------|-----------------------------|------------------------------------|
| <br>COMING SOON | HS1<br>12V 35W/35W PX43t        | <b>Features</b>             | black top color, hardglass, UV-cut |
|  | <b>Ordering Number</b><br>28220 | <b>Standard</b>             | ECE R37                            |
| <b>Product Description</b>   | halogen headlighting lamp       | <b>Typical Applications</b> | low beam, high beam                |

#### TECHNICAL DETAILS

|  |   |   |  |
|--|---|---|--|
| <br>COMING SOON | <b>Rated Voltage</b>  | ECE R37: 12V  |  |
|  | <b>Rated Wattage</b>  | max. 35/35W @13,2V  |  |
|  | <b>Base</b>   | PX43t   |  |
|  | <b>Operating Conditions</b>   | burning position: horizontal, long electrode above filament |  |
|  | <b>Luminous Flux</b>  | 825/525 lm ± 15% @13,2V                                     |  |
| <b>Geometry</b>  | Light center length:<br>28,5mm +0,45mm/-0,25mm<br>Bulb diameter:<br>max. 17mm | <b>Lifetime</b>   | B3: 150/150h @13,2V<br>Tc: 300/300h @13,2V |

#### DELIVERY DETAILS

|                  |   |   |
|------------------|---|---|
| <b>Packaging</b> | Industrial Packaging:<br>200pcs. (5×40)<br>Commercial Box Packaging:<br>100pcs. (10×10×1) | Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture.<br>For use in closed luminaires only. |
|------------------|---|---|

valid from 12/04/2017

replace for -

file 28220 - HS1 12V 35W/35W PX43t.100

**Disclaimer:**  
 Subject to change without notice. Errors and omission accepted.  
 Always make sure to use the most recent release.

**vosla GmbH Plauen Germany**  
[www.vosla.com](http://www.vosla.com)