

Product Information Sheet H11 +50 12V

GENERAL					
	H11 +50 12V 55W PGJ19-2 +50 More Light	Features	original equipment manufacturer quality, high luminance, black top color, green cover plate, hardglass, UV-cut		
	Ordering Number 28478	Standard	ECE R37 DOT		
Product Description	halogen headlighting lamp	Typical Applications	low beam, fog light		
TECHNICAL DETAILS					
Bezugsachse reference axis		Rated Voltage	ECE R37: 12V		
		Rated Wattage	max. 62W @13,2V		

Bezugsebene reference plane		Rated Wattage	max. 62W @13,2V max. 59W @12,8V		
		Base	PGJ19-2		
		Operating Conditions	burning position: horizontal, long electrode above filament		
		Luminous Flux	1350 lm ± 10% @13,2V 1250 lm ± 150lm @12,8V		
Geometry	Light center length: 25mm ± 0,2mm Bulb diameter: max. 12,5mm	Lifetime	B3: 400h @13,2V Tc: 600h @13,2V		
DELIVERY DETAILS					
Packaging	Industrial Packaging: 140pcs. (4×35) Commercial Box Packaging:	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.			

valid from 12.04.2018

replace for 14.08.2017 file 28478 - H11 +50 12V 55W PGJ19-2.100

Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

100pcs. (10×10×1)

vosla GmbH Plauen Germany www.vosla.com