

Product Information Sheet Rally 12V

GENERAL			
	Rally 12V 130W/100W P43t	Features	black top color, hardglass
	Ordering Number 28951	Standard	not regulated
Product Description	halogen headlighting lamp	Typical Applications	low beam, high beam
TECHNICAL DETAILS			
ø17	reference axis	Rated Voltage	12V
	reference plane	Rated Wattage	130W/100W @13,2V
28,5 +0.35		Base	P43t
		Operating Conditions	burning position: horizontal
		Luminous Flux	3200/1800 lm ± 20% @13,2V
Geometry	Light center length: 28,5mm +0,35mm/-0,25mm Bulb diameter: max. 17mm	Lifetime	B3: 225/100h @13,2V Tc: 400/190h @13,2V
DELIVERY DETAILS			
Packaging	Industrial Packaging: 200pcs. (5×40) Commercial Box Packaging: 100pcs. (10×10×1)	pcs. (5×40)mechanical damage, heat and moisture.Immercial Box Packaging:For use in closed luminaires only.	

valid from 12/04/2017 replace for

25.08.2015-V1-PN15/0360

file 28951 - Rally 12V 130W/100W P43t.100

Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

vosla GmbH Plauen Germany www.vosla.com