

## Product Information Sheet W1,2W 24V

GENERAL			
	W1,2W 24V 1,2W W2x4,6d	Features	softglass
	Ordering Number 37040	Standard	not regulated
Product Description	Incandescent signalling and interior lamp with single coil	Typical Applications	indicator, dashboard
TECHNICAL DETAILS			
<u>ø 5,8max.</u>		Rated Voltage	24V
		Rated Wattage	1,2W @28V
15,2 mox.		Base	W2x4,6d
12		Operating Conditions	burning position: horizontal
		Luminous Flux	8,0 lm ± 15% @28V
Geometry	Bulb diameter: max. 5mm	Lifetime	B3: 500h @28V B50: 1000h @28V
DELIVERY DETAILS			
Packaging	Commercial Box Packaging: 200pcs. (20×10)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.	
valid from 23/10/2018	replace for 12/04/2017	, file	37040 - W1.2W 24V 1.2W W2x4.6d.100

valid from 23/10/2018

replace for 12/04/2017

file 37040 - W1,2W 24V 1,2W W2x4,6d.100

## Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

## vosla GmbH Plauen Germany www.vosla.com