

Product Information Sheet T4W 12V

GENERAL				
20 ED 2ND	T4W 12V 4W BA9s	Features	softglass	
	Ordering Number 37131	Standard	ECE R37	
Product Description	Incandescent signalling and interior lamp	Typical Applications	parking light, interior light	
TECHNICAL DETAILS				
15.0 ± 1,5 21,5 max.		Rated Voltage	ECE R37: 12V	
		Rated Wattage	4,4W @13,5V	
		Base	BA9s	
		Operating Conditions	burning position: horizontal	

Geometry

Light center length: 15mm ± 1,5mm Bulb diameter: max. 8,8mm

Rated Voltage	ECE R37: 12V	
Rated Wattage	4,4W @13,5V	
Base	BA9s	
Operating Conditions	burning position: horizontal	
Luminous Flux	35 lm ± 20% @13,5V	
Lifetime	B3: 300h @13,5V Tc: 750h @13,5V	

DELIVERY DETAILS

Packaging

Commercial Box Packaging: 200pcs. (20×10)

Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.

 valid from
 12/04/2017
 replace for
 23.07.2015-V1-PN14/0499
 file
 37131 - T4W 12V 4W BA9s.100