

## Product Information Sheet R5W 12V

GENERAL				
NIA ROM 12U(E).	R5W 12V 5W BA15d		Features	softglass
	Ordering Number 37172		Standard	ECE R37
Product Description	Incandescent signalling lamp		Typical Applications	rear light, parking light
TECHNICAL DETAILS				
	а 19,0 max. 30,0 max.		Rated Voltage	ECE R37: 12V
			Rated Wattage	max. 5,5W @13,5V
51			Base	BA15d
19,0±1,5			Operating Conditions	burning position: horizontal
			Luminous Flux	50 lm ± 20% @13,5V
Geometry	Light center length: 19mm ± 1,5mm Bulb diameter: max. 19mm		Lifetime	B3: 150h @13,5V Tc: 400h @13,5V
DELIVERY DETAILS				
Packaging	Commercial Box Packaging: 200pcs. (20×10)		Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.	
valid from 13/11/2018	replace for	24/10/2017	file	37172 - R5W 12V 5W BA15d.100

## Disclaimer:

Subject to change without notice. Errors and omission accepted. Always make sure to use the most recent release.

## vosla GmbH Plauen Germany www.vosla.com