



#### GENERAL

 COMING SOON	P27W 12V 27W W2,5x16d 3156	<b>Features</b>	softglass
	<b>Ordering Number</b> 37941	<b>Standard</b>	ECE R37 ANSI
<b>Product Description</b>	Incandescent signalling lamp	<b>Typical Applications</b>	indicator, rear fog light, stop light

#### TECHNICAL DETAILS

 COMING SOON	<b>Rated Voltage</b>	ECE R37: 12V	
	<b>Rated Wattage</b>	32,1W @13,5V	
	<b>Base</b>	W2,5x16d	
	<b>Operating Conditions</b>	burning position: horizontal	
	<b>Luminous Flux</b>	475 lm ± 15% @13,5V	
<b>Geometry</b>	Light center length: 27,9mm Bulb diameter: max. 26,5mm	<b>Lifetime</b>	B3: 550h @13,5V Tc: 1320h @13,5V

#### DELIVERY DETAILS

<b>Packaging</b>	Commercial Box Packaging: 200pcs. (20×10)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.
------------------	--	---

valid from 12/04/2017

replace for -

file 37941 - P27W 12V 27W W2,5x16d.100

**Disclaimer:**  
 Subject to change without notice. Errors and omission accepted.  
 Always make sure to use the most recent release.