



#### GENERAL

	<b>PY27/7W</b> 12V 27W/7W WX2,5x16q 3157NA	<b>Features</b>	natural amber, softglass
	<b>Ordering Number</b> 37948	<b>Standard</b>	ECE R37 ANSI
<b>Product Description</b>	Incandescent signalling lamp	<b>Typical Applications</b>	combined indicator and rear light

#### TECHNICAL DETAILS

  COMING SOON	<b>Rated Voltage</b>	ECE R37: 12V
	<b>Rated Wattage</b>	32,1W/8,5W @13,5V
	<b>Base</b>	WX2,5x16q
	<b>Operating Conditions</b>	burning position: horizontal
	<b>Luminous Flux</b>	280/21 lm ± 15% @13,5V
	<b>Lifetime</b>	B3: 550/3600h @13,5V Tc: 1300/8000h @13,5V
<b>Geometry</b>	Light center length: 27,9mm Bulb diameter: max. 26,5mm	

#### DELIVERY DETAILS

<b>Packaging</b>	Commercial Box Packaging: 200pcs. (20×10)	Handle with care. Please store up and install the lamps free of mechanical damage, heat and moisture. For use in closed luminaires only.
------------------	--	---

valid from 19.10.2018

replace for 12/04/2017

file 37948 - PY27/7W 12V 27W/7W WX2,5x16q.100

**Disclaimer:**  
 Subject to change without notice. Errors and omission accepted.  
 Always make sure to use the most recent release.